

MD HIGH RANGE DP

RANGE SELECTION TABLE

Range Code	Range bar (psi)	Differential* bar (psi)	Maximum Working Pressure bar (psi)
		Approximate Maximum for "A1" microswitch	
D01	0.1 - 1.0 (1.45 - 14.50)	0.12 (1.74)	70 (1015.26)
D02	0.1 - 1.5 (1.45 - 21.76)	0.20 (2.90)	70 (1015.26)
D03	0.2 - 2.6 (2.90 - 37.71)	0.20 (2.90)	70 (1015.26)
D04	0.2 - 3.6 (2.90 - 52.21)	0.30 (4.35)	70 (1015.26)
D07	0.5 - 7.0 (7.25 - 101.50)	0.40 (5.80)	70 (1015.26)
D10	0.5 - 10.0 (7.25 - 145.04)	0.50 (7.25)	70 (1015.26)
D15	1.0 - 15.0 (14.50 - 217.71)	0.50 (7.25)	70 (1015.26)
D30	5.0 - 25.0 (72.52 - 362.6)	0.80 (11.60)	70 (1015.26)

*Minimum differential increases with setpoint (Graphs available on request)

*** Note :**

Microswitches A2 through A9 can be supplied in some ranges and differentials will vary with microswitch used. Please contact sales office for details. Please check availability of adjustable differential with sales office.